



## Acme Sanitary Ware Co Ltd

Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong  
 Tel: 2388 7171 Fax: 2710 8012  
 E-mail: acme@acmesanitary.com.hk  
 Website: www.acmesanitaryware.com.hk



**WORK  
SMARTER**

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

## SANITARY WARE SPECIFICATION SHEET

Item Descriptions	GROHE (Germany) "SmartControl 360 MONO" chrome plated showersystem with thermostat for wall mounting shower mixer and white hand shower;Nominal flow rate 8 l/min in WELS Grade 1 ; Registration No. SB 17-0036					Illustration/ Drawing												
Dimensions	Height: 1200 mm																	
Model	26361000																	
Finish	Chrome Plated																	
Manufacturer	GROHE Limited																	
Country of Origin	Germany																	
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Wilson Hung																	
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012																	
E-mail	acme@acmesanitary.com.hk																	
Website	www.acmesanitary.com.hk																	
<table><tr><td>Dynamic flow pressure (kpa)</td><td>50</td><td>150</td><td>250</td><td>350</td><td>500</td></tr><tr><td>Average Flow Rate l / min</td><td>5.4</td><td>7.9</td><td>8.4</td><td>8.6</td><td>8.7</td></tr></table> <p>consisting of: horizontal 500 mm shower arm, exposed SmartControl thermostat allows change between: head shower Rainshower 360 MONO, spray plate chrome <b>GROHE PureRain/GROHE Rain O<sup>2</sup> spray*</b> 27673LS0 Power&amp;Soul 130 hand shower, spray plate white 27055000 hand shower wall holder 28388000 Silverflex shower hose 1750 mm minimum flow rate 10 l/min. <b>GROHE DreamSpray®</b> perfect spray pattern <b>GROHE StarLight</b> chrome finish <b>GROHE CoolTouch®</b> no risk of scalding <b>GROHE TurboStat®</b> compact cartridge with wax thermoelement <b>GROHE EcoJoy®</b> technology for less water and perfect flow <b>GROHE SafeStop</b> safety button at 38°C <b>GROHE SafeStop Plus</b> (optional) additional temperature limiter at 43° C <b>GROHE SmartControl</b> push for ON-OFF, turn for volume adjustment from EcoJoy to Full Flow <b>GROHE EasyReach</b> shower tray SpeedClean anti-lime system Inner WaterGuide for a longer life Twistfree to prevent hose from twisting</p>						Dynamic flow pressure (kpa)	50	150	250	350	500	Average Flow Rate l / min	5.4	7.9	8.4	8.6	8.7	
Dynamic flow pressure (kpa)	50	150	250	350	500													
Average Flow Rate l / min	5.4	7.9	8.4	8.6	8.7													
																		
																		

Note: hand shower 27673XXX where XXX is colour code XXX = LS0 ( white ) XXX = 000 ( chrome )

\* All information of the above is for the reference only. No prior notice is made if any changes.



## Acme Sanitary Ware Co Ltd

Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong  
 Tel: 2388 7171 Fax: 2710 8012  
 E-mail: acme@acmesanitary.com.hk  
 Website: www.acmesanitaryware.com.hk



Pure Freude  
an Wasser

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

## SANITARY WARE SPECIFICATION SHEET

Item Descriptions	GROHE (Germany) "Power&Soul® 130 " chrome plated 4-Sparys hand shower; Nominal flow rate 8 l/min in WELS Grade 1 ; Registration No. SB 17-0036					<div>Illustration/ Drawing</div> <div></div>												
Dimensions	Refer to drawing																	
Model	27673LS0																	
Finish	Chrome Plated																	
Manufacturer	GROHE Limited																	
Country of Origin	Germany																	
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Wilson Hung																	
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012																	
E-mail	acme@acmesanitary.com.hk																	
Website	www.acmesanitary.com.hk																	
<table><tr><td>Dynamic flow pressure (kpa)</td><td>50</td><td>150</td><td>250</td><td>350</td><td>500</td></tr><tr><td>Average Flow Rate l/min</td><td>5.4</td><td>7.9</td><td>8.4</td><td>8.6</td><td>8.7</td></tr></table>						Dynamic flow pressure (kpa)	50	150	250	350	500	Average Flow Rate l/min	5.4	7.9	8.4	8.6	8.7	
Dynamic flow pressure (kpa)	50	150	250	350	500													
Average Flow Rate l/min	5.4	7.9	8.4	8.6	8.7													
<div>Power&amp;Soul 130</div> <div>Hand shower 4+ sprays, spray plate night time grey</div> <div>GROHE Rain O², Rain, Bokoma Spray, Jet</div> <div>GROHE EcoJoy 9.5 l/min flow limiter</div> <div>GROHE DreamSpray perfect spray pattern</div> <div>GROHE One-click showering</div> <div>push button spray selection</div> <div>GROHE StarLight chrome finish</div> <div>SpeedClean anti-limescale system</div> <div>Inner WaterGuide for a longer life</div> <div>Universal Mounting System. Fits all standard shower hoses</div> <div></div>						<div></div>												

Note: hand shower 27673XXX where XXX is colour code XXX = LS0 ( white ) XXX = 000 ( chrome )

\* All information of the above is for the reference only. No prior notice is made if any changes.



自願參與用水效益標籤計劃 - 沐浴花灑  
Voluntary Water Efficiency Labelling Scheme - Showers for Bathing


*Certificate of Registration* 註冊證書

茲證明  
This is to certify that

Grohe Hong Kong Limited

將下列花灑在本計劃內註冊：  
has registered the following shower under this scheme :

牌 子 / Brand	:	GROHE
型 號 / Model	:	27673000
原產地 / Country or Region Origin	:	Germany

在用水效益標籤上展示的標誌 <i>Symbolic Presentation on the Water Efficiency Label</i>	:	 滴水點 <i>Water droplet(s)</i>
用水效益級別 <i>Water Efficiency Grade</i>	:	1
耗水量 <i>Water Consumption</i>	:	8 公升/分鐘 <i>litres/minute</i>

簽發日期: 12 September 2017  
Date of Issue:



水務署  
Water Supplies Department



水務署署長(周世威代行)  
for Director of Water Supplies



水務署

Water Supplies Department

香港灣仔告士打道七號入境事務大樓  
Immigration Tower, 7 Gloucester Road, Hong Kong

電子郵件  
e-mail [wsdinfo@wsd.gov.hk](mailto:wsdinfo@wsd.gov.hk)

電話  
Telephone 2829 4355

圖文傳真  
Facsimile 2824 0578

檔號  
Reference (4) in WSD 3321/17 Pt.1 T/J(1154)

25 September 2017



### Approval of “GROHE” Thermostatic Blending Valve

Your letters ref. WRC/1483 and C-WSD/0295 dated 25 August 2017 and 1 September 2017 respectively refer.

It is noted that the fitting described below has been accepted by the United Kingdom Water Regulations Advisory Scheme (WRAS) to have complied with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations / Scottish Water Byelaws when correctly installed.

**Name of Manufacturer:** Grohe AG

**Country of Origin:** Germany

**Brand:** Grohe

**Details of Fitting:** Wall mounted, exposed, thermostatic blending valve (chrome plated brass). The flow is controlled to the shower via independent ‘detent’ (push to on push to off) headworks, that also incorporates a quarter turn ceramic disc (rotary control) to adjust the volume of water. The temperature is controlled independently via a thermostatic cartridge with a dome type operating member that incorporates a manual override button.

Maximum working pressure 10.0 Bar. Maximum operating temperature 60°C.

**Model:** 26.361

**Size:** ½" BSP (M)

**Marking:**  on the body of the valve

**WRAS Approval Number:** 1703021

**Installation Requirements:** R001, R040

**Expiry Date:** 31 March 2022

In view of the acceptance by WRAS, this Authority has no objection to the use of the said fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following installation requirements –

“Installation shall comply with the ‘Installation Requirements & Notes’ of the WRAS’s approval letter concerned.”

“The cold water supply to the fitting shall be drawn from the same source that supplies the hot water apparatus so as to provide a balanced pressure and to obviate the risk of scalding in the event of a restriction or failure in the water supply.” AND

“The shower head or handspray should not be placed in submerged conditions and should be securely fixed to the original position after use.”

A condition of this acceptance is that the fitting to be installed should be replicas of the sample certified by WRAS and no modification should be made to the fitting. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fitting, unless other specified.

For the use of the fitting in any project, the Acceptance Reference Number at the bottom of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.