


Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong Tel: 2388 7171 Fax: 2710 8012 Email: acme@acmesanitary.com.hk Since 1949 Website: www.acmesanitary.com.hk

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Bobrick (USA) Surface mounted towel bar		
Dimensions	Refer to drawing		
Model	B-6737X24		
Material/ Finish	Stainless Steel/ Satin Finish		
Manufacturer	Bobrick Washroom Equipment Inc. (USA)		
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen		
Contact Tel/Fax E-mail Website	(852) 2388-7171 / (852) 2710-8012 acme@acmesanitary.com.hk www.acmesanitary.com.hk		



Materials:

Flanges and Support Arms (2) — 18-8, type-304, 22-gauge (0.8mm) stainless steel. Each flange has concealed, 16-gauge (1.6mm) stainless steel mounting bracket. All-welded construction. Secured to wall plates with stainless steel locking set-screws.


Concealed Wall Plates (2) — 18-8, type-304, 16-gauge (1.6mm) stainless steel. **Towel Bar** — 18-8, type-304, heavy-gauge stainless steel. Lockseam rolled, 3/4" (19mm) square tubing.

installation:

To remove concealed wall plates from back of flanges and mounting brackets, loosen locking setscrews. Mount each wall plate so prongs are at top; secure with two sheet-metal screws, furnished by manufacturer, at points indicated by an S. Engage mounting brackets onto prongs of wall plates, then secure into position by tightening locking setscrews at bottom of flanges.

Note: Centerline-to-centerline of concealed wall plates must be within 1/16" (1.6mm) of the Y dimension given.

For plaster or dry wall construction, provide concealed backing to comply with local building codes, then secure unit with screws furnished. For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws furnished, or provide 1/8" (3mm) toggle bolts or expansion bolts.



Model No.	Bar Length L	Overall Length X	Centerline- to-Centerline Y
B-673 x 18	18" (455mm)	19-5/8" (500mm)	17-5/8" (450mm)
B-673 x 24	24" (610mm)	25-5/8" (650mm)	23-5/8" (600mm)
B-6737 x 24	24" (610mm)	25-5/8" (650mm)	23-5/8" (600mm)

Note: