

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	WDI (PRC) Adjustable single top push flush	Illustration/ Drawing			
	valve				
Dimensions	Refer to drawing	Single			
Model	B4018				
Material	Plastic				
Manufacturer	WDI (PRC)				
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen				
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012				
E-mail	acme@acmesanitary.com.hk				
Website	www.acmesanitary.com.hk				
		Ø80.9 Ø49.7 86 953 Ø60			
		<u>_</u> Ø90.3 <u>_</u>			

Note: The color of the above fittings may be varied without further notice.

^{*} All information of the above is for the reference only. No prior notice is made if any changes.



本署檔號

(6) in WSD 3321/2020 T/J(1073/2020)

電話

Tel.

來函檔號 Your ref.

傳真 Fax.

: 2824 0578

10 February 2021

Dear Madam,

Approval of "WDI" Flush Valve (General Acceptance No. C20210127F)

Your letter ref. J25120 (B4018) dated 12 August 2020 and subsequence submissions received by this department up to 27 November 2020 refer.

Having considered the test report ref. J25120 issued on 4 August 2020 by Ideal Test Consultants Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

ECO (Xiamen) Technology Inc

Country of Origin:

the Mainland of China

Brand:

WDI

Details of Fitting:

2" Plastic single flush valve

Model:

B4018

Body Markings:

SASO1480 B4018

Expiry Date:

5 February 2025





Proviso:

As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

"The fitting should be used within the range of working pressures specified by the manufacturer." AND

"The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(CHAN Chung-kun)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue ME/MC] - with soft copy only