




Acme Sanitary Ware Co Ltd

Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong
 Tel: 2388 7171 Fax: 2710 8012
 E-mail: acme@acmesanitary.com.hk
 Website: www.acmesanitaryware.com.hk

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Hand dryer Junior sensor operated, white ABS	<div>Illustration/ Drawing</div> <div></div>
Dimensions	L252 x W133 x H300 mm	
Model	M88A	
Material/ Color	ABS/ White	
Manufacturer	Mediclinics, S.A. (Spain)	
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Wilson Hung	
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012	
E-mail	acme@acmesanitary.com.hk	
Website	www.acmesanitary.com.hk	
<div>Components and Materials</div> <ul style="list-style-type: none">• White ABS thermoplastic one-piece cover, 3 mm thick. Cover fixed to the base by means of 4 Phillips head screws.• Thermoplastic PP+ talcum base, with 4 Ø 8 mm holes for wall mounting.• Induction motor, 2.800 rpm, maintenance-free and high durability, incorporates a self-resetable thermal cut-off at 130 °C.• PP UL94-VO with single inlet fan wheel.• Waved wire NiCr heating element that incorporates a self-resetable thermal cut-off at 80 °C.• Two distances (15/25 cm) IR electronic detection sensor.• Stainless steel air outlet grill. <div>Operation</div> <p>Place the hands under the air outlet grill. The dryer will start automatically, and go on with no interruption as long as the hands are kept in the detection range of the sensor. The appliance will stop 2 seconds after the hands are removed from the airflow.</p>		

Voltage	220-240 V
Frequency	50/60 Hz
Electrical isolation	Class II
Dimensions	300x 252x 133 mm
Weight	3 Kg
Effective airflow	160 m³/h / 2.670 l/min
Nominal airflow	200 m³/h 3300 l/min
Air velocity	60 Km/h
Total power	1.650 W
Motor power	140 W
Heating element power	1.510 W
Consumption	7 A
RPM	2.800
Air temperature(10 cm distance / 21 °C)	51 °C
Noise level (at 2 m)	60 dB
Protection level	IP23

Note: