

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Haws (USA) circular concrete pedestal	Illustration/ Drawing		
	drinking fountain with front-operated push button	(f) Haws		
Model	3060			
Material	Concrete	ACME 102mm		
Manufacturer	Haws Corporation (USA)			
Source	Acme Sanitary Ware Co. Ltd	3X1/2"-13 UNC 1054mm 3X1/2"-13 UNC 0UTLET)		
	Mr. Eric Wong/ Mr. Wilson Hung	MTG HARDWARE (SUPPLIED)		
	The Wong, I'm Winson Hong			
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012			
E-mail	acme@acmesanitary.com.hk			
Website	www.acmesanitary.com.hk	BUBBLER LOCATION SUPPLY WASTE 64mm 305mm 3x 1/2" MTG BOLTS ON 229mm B.C.		
operated stainless steel valve wi	ing fountain shall include a polished stainless steel basin, push-button th front-accessible cartridge and flow adjustment, polished chrome-plated ead protected by a hood extension, polished chrome-plated vandal-	127mm x 152mm ACCESS PLATE BIB FAUCET OR AHOSE BIB (OPTIONAL)		
resistant waste strainer, Portland	d Gray exposed aggregate concrete finish with wire reinforcement, integral stainless steel access plate, and 1-1/4" O.D. tailpiece.	SEE BIS DETAIL COUPLINGS (NOT SUPPLIED)		
Features & Benefits: BUBBLER HEAD		3X		
Polished chrome-plated brass busteady sanitary source of water.	ubbler head is equipped with a shielded, anti-squirt orifice that provides a	MOUNTING HOLE PLUGS SECURED WITH EPOXY (EPOXY NOT SUPPLIED) GROUND LEVEL		

Note:			

With its patented (Pat.# 6,981,692) stainless steel, push-button activated valve assembly which allows for front access stream adjustment as well as cartridge and strainer access, this fountain offers 100% lead free

waterways. The valve works at an operating pressure range of 30 to 90 psi.

PUSH BUTTON

1/2" IPS SUPPLY (NOT SUPPLIED)