



Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong
 Tel: 2388 7171 Fax: 2710 8012
 Email: acme@acmesanitary.com.hk
 Website: www.acmesanitary.com.hk



Pure Freude
an Wasser

PROJECT		REF		REV	ITEM CODE	
LOCATION		DATE			PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	GROHE (Germany) "Eurosmart Cosmopolitan E" Infra-red electronic basin tap 1/2" in DC Supply ; nominated flow rate 1.7 L/min in WELS Grade 1 ; Registration No. TN 18-0036					<div>Illustration/ Drawing</div> <div></div>												
Dimensions	L144 x W42 x H132 mm																	
Model	36439000 (Sensor Tap) A5.9042.1 (Aerator)																	
Finish	Chrome Plated																	
Manufacturer	GROHE Limited																	
Supplier	Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen																	
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012																	
E-mail	acme@acmesanitary.com.hk																	
Website	www.acmesanitary.com.hk																	
<table><tr><td>Dynamic flow pressure (kPa)</td><td>50</td><td>150</td><td>250</td><td>350</td><td>500</td></tr><tr><td>Flow rate (l / min)</td><td>1.10</td><td>1.55</td><td>1.70</td><td>1.75</td><td>1.80</td></tr></table> <p>with infrared sensor for bi-directional communication for monitoring, configuration and servicing for cold or premixed water 6V lithium-battery, type CR-P2 battery lifetime approx. 7 years (150 actuations a day) GROHE StarLight chrome finish GROHE EcoJoy mousseur 5.7 l/min flexible connection hose dirt strainer with integrated solenoid valve external battery rapid installation system multistage battery status display 7 pre-set programs auto flush thermal disinfection cleaning mode additional functions and precise settings by remote control 36 407 CE approved noise classification 1 in accordance with DIN4109 type of protection faucet IP 59K</p>						Dynamic flow pressure (kPa)	50	150	250	350	500	Flow rate (l / min)	1.10	1.55	1.70	1.75	1.80	<div></div>
Dynamic flow pressure (kPa)	50	150	250	350	500													
Flow rate (l / min)	1.10	1.55	1.70	1.75	1.80													

* All information of the above is for the reference only. No prior notice is made if any changes.



自願參與用水效益標籤計劃 - 水龍頭
Voluntary Water Efficiency Labelling Scheme - Water Taps



茲證明
This is to certify that

將下列水龍頭在本計劃內註冊：
has registered the following water tap under this scheme :

牌 子 / Brand	:	GROHE
型 號 / Model	:	36439000 + A5.9042.1
種 類 / Type	:	Non-mixing
原產地 / Country or Region Origin	:	Germany

在用水效益標籤上展示的標誌

Symbolic Presentation on the Water Efficiency Label



滴水點

Water droplet(s)

用水效益級別

Water Efficiency Grade

: 1

with additional merit*

耗水量

Water Consumption

: 1.7

公升/分鐘

litres/minute

*with additional merit of "Automatic closing mechanism"

簽發日期:

6 July 2018

Date of Issue:



水務署

Water Supplies Department



水務署署長(周世威代行)
for Director of Water Supplies



水務署
Water Supplies Department

總部 Headquarters

香港灣仔七打道七號入境事務大樓 48 樓

Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號
Our ref.
來函檔號
Your ref.



2022 T/J(1326/2022)

電話 :
Tel.
傳真 : 2824 0578
Fax.

15 December 2022



**Approval of "GROHE" Sensor Tap
(General Acceptance No. C20221144)**

Your letter ref. WRC/2818 dated 24 November 2022 refers.

Having considered the test report ref. 221005PC220175 issued on 16 November 2022 by Fugro Technical Services Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer: Grohe AG

Country of Origin: Germany

Brand: Grohe

Details of Fitting: 3/8" Deck mounted sensor tap

Model: 36439XXX
(where "XXX" denotes the code of colour)

Body Markings: **GROHE**


Expiry Date: 12 September 2027



This Authority hereby permits the use of the above fitting in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"A stop cock or gate valve must be installed at the upstream of the fitting for manual isolation of water supply." AND

"The main voltage operated sensor valve should comply with the electricity safety regulation for applications in bathroom, toilet etc."


A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fitting, unless otherwise specified.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Ms Winnie LO at tel. no. 3583 4086.

Yours faithfully,



(YAU Hau Yin)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
 ME/MC] - with soft copy only