

## Acme Sanitary Ware Co. Ltd.

1/F, Acme Building, 22-28 Nanking Street, Kowloon, Hong Kong Tel: 2388 7171 Fax: 2710 8012 Email: acme@acmesanitary.com.hk

Website: www.acmesanitary.com.hk

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

## SANITARY WARE SPECIFICATION SHEET

Item Descriptions Bobrick (USA) "Classic Series" Partition mounted dual sided multi-roll toilet tissue dispenser (serves two toilet compartments) Model B-386 Material/Finish Heavy-duty cast aluminum/ Satin Manufacturer Bobrick Washroom Equipment Inc. (USA) Supplier Acme Sanitary Ware Co. Ltd Mr. Eric Wong/ Mr. Don Yuen Contact Tel/Fax (852) 2388-7171 / (852) 2710-8012 E-mail acme@acmesanitary.com.hk Website www.acmesanitary.com.hk

## MATERIALS:

Cabinet — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel. All-welded construction. Exposed surfaces have satin finish.

Flanges (2) — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel with satin finish. Drawn and beveled, one-piece, seamless construction.

Toilet Tissue Dispensers (4) — 18-8 S, Type-304, 22 gauge (0.8mm) stainless steel with satin finish. Holds two standard-core toilet tissue rolls up to 5-1/8" (130mm) diameter (1500 sheets) for each toilet compartment.

Spindles (4) — Chrome-plated plastic, equipped with heavy-duty internal springs.

Designer's Note: Theft-resistant spindles, which are removable only with special key provided. Order Part Number 283-604.

## OPERATION:

Unit holds four standard-core toilet tissue rolls up to 5-1/8" (130mm) diameter (1500 sheets), two for each compartment. Spindles may be removed from each compartment for servicing.

Designers Note: It is recommended that one full toilet tissue roll remain wrapped until the other roll has been depleted to avoid wasting ends of both rolls.

Mount unit, with seam in wrapper at bottom, in toilet partition 1/2" to 2" (13 to 50mm) thick, centered through a cutout specially ordered from partition manufacturer or field cut. Dimensions of cutout are to be 11-1/2" wide x 10-7/8" high (290 x 275mm). For factory-made cutouts, location and size details should be furnished to partition manufacturer. For hollow-core metal partitions, provide solid framing into which sheet-metal mounting screws can be secured. For installation with sheet-metal screws furnished, place unit firmly in partition cutout, making certain that entire perimeter of fixed flange is flush with and tight against partition surface. Secure to partition with screws through four mounting holes at points indicated by an S. On other side of partition, position adjustable flange (which ser ves as an escutcheon) so mounting holes are not in-line with mounting holes in fixed flange. Make certain entire perimeter of adjustable flange is flush with and tight against partition surface before securing with sheet-metal screws furnished by manufacturer.

Note: Cutouts in Bobrick toilet partitions can be pre-cut for Bobrick partition-mounted accessories at factor y if location and size of cutouts are specified and the order for both partitions and accessories are received together.

### SPECIFICATION:

Partition-mounted dual-sided multi-roll toilet tissue dispenser shall be Type-304 stainless steel with allwelded construction; exposed surfaces shall have satin finish. Flanges shall be drawn and beveled, onepiece, seamless construction. Unit shall mount in toilet partition and shall ser ve two toilet compartments. Unit shall dispense four standard-core toilet tissue rolls up to 5-1/8" (130mm) diameter (1500 sheets). \*Spindles shall be equipped with a heavy-duty internal spring.

# Illustration/ Drawing BOBRICK 10-9/16" 270mm 12-1/16" 11-1/4" 520mm to Back of Wall -1/2" 4" — Adjustable Flange Ġ Recommended Mounting Height Off I ended Mounting Height Off I for Barrier-Free Design 36" 915mm 27-1/2" Fixed Flange **Rough Partition Cutout** 11-1/2" (290mm) wide

## \* All information of the above is for the reference only. No prior notice is made if any changes.

10-7/8" (275mm) high

1/2" to 2" (12 to 50mm) partition thickness