

PROJECT	REF	REV	ITEM CODE	\bigcirc
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Sloan infra-red sensor flush valve in battery	Illustration/ Drawing
	operated for sea water applications (HKWA	SLOAN
	Approved)	
Power	Four alkaline batteries (AA size)	
Sensor Range	Nominal 203-711 mm, adjustable±254 mm	
Solenoid Valve	6V DC w/ integral strainer filter & 1/2"	
	pipe connection inlet/ outlet	
Battery Life	2 years at 4000 cycles/ months	SLOAN
Indicator Lights	Range adjustment/ low battery	
Operating Pressure	Range 21-862 kPa/ 3-125 psi/ 0.2-8.6 Bar	
Flush Cycle	Adjustable: 1-15 seconds	
Flush Discharge	1.0 Lpf @ 3 seconds*	
Pre-flush	1 second pre-flush after user is detected	
	for 2 seconds (optional)	153 mm (6.02') 100 mm (3.93')
Sentimel Flush	Automatic flush once 24 hours after last flush	173 mm 0 (6.81)
	(optional)	(1021) 1021P.S. OUTLET 265 mm (10.43')
Dimensions	W153 x H173 mm	75 mm (2.957)
Model	ELG-130	
Finish	Chrome Plated	1160 mm (45.67') CENTERLINE
Manufacturer	Sloan (USA Brand)	FINISHED FLOOR
		WALL BOX PRISED WILL INVERT SERVICED
Supplier	Acme Sanitary Ware Co. Ltd	WALL BOX INSTALLATION FRISHED WILL SECOND VIVE BXX
	Mr. Eric Wong/ Mr. Wilson Hung	
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012	
E-mail	acme@acmesanitary.com.hk	
Website	www.acmesanitary.com.hk	LIP POSITIONED TO BOTTOM

Note: