

PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	Star (Thailand) "Monica" Vitreous china high-P trap bowl, w/ "Soluna" close-coupled (Top Push) tank	Illustration/ Drawing
Dimensions	L690 x W420 x H776 mm	
Model	S-2585 (Water Closet)	
	S-3508.5 (Cistern)	
Material/ White	Vitreous China/ White	
Manufacturer	Star (Thailand)	
Source	Acme Sanitary Ware Co. Ltd	690
	Mr. Eric Wong/ Mr. Don Yuen	632
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012	Ø105
E-mail	acme@acmesanitary.com.hk	190 08 390
Website	www.acmesanitary.com.hk	
		420 Ø40
		370 Ø15 140
		776 152 435 325
		210
		FINSHED FLOOR 222 355

Note:



PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions	WDI (PRC) Adjustable plastic inlet valve	Illustration/ Drawing
Dimensions	Refer to drawing	00
Model	B3800E	
Material	Plastic	
Manufacturer	WDI (PRC)	
Supplier	Acme Sanitary Ware Co. Ltd	
	Mr. Eric Wong/ Mr. Don Yuen	
Contact Tel/Fax	(852) 2388-7171 / (852) 2710-8012	
E-mail	acme@acmesanitary.com.hk	
Website	www.acmesanitary.com.hk	60 98 26.5 82 0000 60 98 26.5 87 000 000 87 000 000

Note: The color of the above fittings may be varied without further notice.

^{*} All information of the above is for reference only. No prior notice is made if any changes.





本署檔號 Our ref. 來函檔號

Your ref.

: (4) in WSD 3321/2020 T/J(401/2020)

電話 Tel.

傳真 Fax.

: 2824 0578

23 June 2020

Approval of "WDI" Float Operated Valve (General Acceptance No. C20200498F)

Your letters ref. BE/L20319/20 and BE/L20359/20 dated 15 April 2020 and 22 May 2020 respectively refer.

Having considered the test report ref. RACA059rl issued on 19 May 2020 by Ideal Test Consultants Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

WDI (Xiamen) Technology Inc

Country of Origin:

the Mainland of China

Brand:

WDI

Details of Fitting:

1/2" Plastic float operated valve

Model:

B3800E

Body Markings:

WDI

Expiry Date:

25 March 2025





Proviso:

As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

> "The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

> "The fitting should be used within the range of working pressures specified by the manufacturer." AND

> "The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(CHAN Chung-kun)

for Director of Water Supplies

Encl.

C.C. WSD 3321/1/82] - without catalogue ME/MC

] - with soft copy only



PROJECT	REF	REV	ITEM CODE	
LOCATION	DATE		PAGE	

SANITARY WARE SPECIFICATION SHEET

Item Descriptions WDI (PRC) Adjustable 3/6L dual flush valve Illustration/ Drawing with lockable design for cistern lid Dimensions Refer to drawing Model B4900H Material Plastic WDI (PRC) Manufacturer Acme Sanitary Ware Co. Ltd Supplier Mr. Eric Wong/ Mr. Don Yuen (852) 2388-7171 / (852) 2710-8012 Contact Tel/Fax E-mail acme@acmesanitary.com.hk Website www.acmesanitary.com.hk height of overflow pipe 268 Φ60 118 UPC) (IP)

Note: The color of the above fittings may be varied without further notice.

^{*} All information of the above is for the reference only. No prior notice is made if any changes.



本署檔號 Our ref. 來函檔號

Your ref.

(4) in WSD 3321/2020 T/J(399/2020)

電話

Tel.

傳真 Fax.

2824 0578

15 June 2020

Approval of "WDI" Flush Valve (General Acceptance No. C20200454F)

Your letters ref. BE/L20317/20 and BE/L20354/20 dated 15 April 2020 and 19 May 2020 respectively refer.

Having considered the test report ref. RACA058 issued on 9 April 2020 by Ideal Test Consultants Ltd., this Authority accepts that the fitting described below complies with, and its use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer:

WDI (Xiamen) Technology Inc

Country of Origin:

the Mainland of China

Brand:

WDI

Details of Fitting:

2" Plastic dual flush valve

Model:

B4900H

Body Markings:

WDI B4900

Expiry Date:

2 April 2025





Proviso:

As the fitting has not been tested for use in contact with water intended for human consumption, the fitting can only be used in flushing water plumbing system.

This Authority hereby permits the use of the above fitting in flushing water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following requirement-

"The flushing volume of the flushing valve should be adjusted to suit the design of the toilet bowl so that wastes can be cleared effectively by a single flush."

"The fitting should be used within the range of working pressures specified by the manufacturer." AND

"The installed fitting should not result in backflow of water that will contaminate the flushing water supply."

A condition of this acceptance is that the fitting to be installed shall be replicas of the sample as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fitting installed fails to meet that of the approved sample or if the fitting is found to be unsuitable for use in flushing water plumbing systems.

For the use of the fitting in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fitting by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,

(CHAN Chung-kun)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue

] - without catalogue] - with soft copy only

ME/MC